

TECHNICAL DATA SHEET



SYNTHETIC SAE 5W-30

EUROPEAN FORMULA

PRODUCT # 10206

TEST

ASTM

TYPICAL

| | | |
|--------------------------------|---------------|--------------------|
| API Gravity | D-1298 | 33.82 |
| Specific Gravity @ 60°F | D-1298 | 0.856 |
| Density @ 60°F, lb/gal | D-1298 | 7.14 |
| CCS @ -30°C, CPS | D-5293 | 6,600 Max |
| MRV @ -35°C, CPS | D-4684 | 60,000 Max |
| Zinc, WT% | X-ray | 0.085 |
| TBN, Mg KOH/g | D-2896 | 7.5 |
| Viscosity @ 40°C cSt | D-445 | 57.5 |
| Viscosity @ 100°C cSt | D-445 | 11.1 |
| Viscosity Index | D-2270 | 174 |
| Flash Point, COC °F | D-92 | 430 |
| Color | | Light Brown |

Lucas Synthetic SAE 5W-30 Motor Oil is especially formulated for high mileage or high performance engines; it is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.

Lucas Synthetic SAE 5W-30 Motor Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.

Lucas Synthetic SAE 5W-30 Motor Oil is the perfect lubricant for high RPM and high temperature engines. The exclusive additive package in Lucas Synthetic SAE 5W-30 Motor Oil allows for extended drain intervals.

Lucas Synthetic SAE 5W-30 Motor Oil far exceeds all OEM specifications. Formulated to meet ALL motor that calls for a Synthetic SAE 5W-30 motor oil.

Meets or exceeds American and European OEM specifications API SM/SL/SJ/CF, ACEA A5/B5-04, A3/B4-04, C2-08, C3-07, C2-04, MB 229.31, MB 229.51, VW 50200, 50500, 50501, BMW Longlife-04, Porsche, Ford WSS M2 C 917 A. Suitable for use where VW 50700 is recommended.