

### LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

## SLICK MIST® CERAMIC SPEED WAX



Slick Mist® Ceramic Speed Wax is a Professional Paint Sealant and Durable Protectant anyone can use. May also be used on gel coat, glass and chromed surfaces. Overspray will not harm rubber and plastic trim. Also works great on aluminum surfaces, vinyl wraps, PPF, matte finishes and ceramic coated surfaces. We recommend use everyone to two months. 100% compatible with Lucas Slick Mist® Speed Wax.

#### PART NUMBER AND SIZE:

11294 – 24 oz (710 mL) 21294 CAN – 24 oz (710 mL)

#### FEATURES AND BENEFITS:

- A Professional Si02 Hybrid Ceramic Paint Sealant
- UV Resistant
- Super Glossy Appearance, Beading and Protection
- Instant Results
- Long Lasting
- Completely Cures in Hours
- Overspray will NOT Harm or Stain Rubber or Plastic Trim

#### DIRECTIONS FOR USE:

- Shake Well Before Using
- Use on a Clean Wet or Dry Painted Surface
- Spray on Liberally and Wipe Dry with a Clean Soft Microfiber Towel
- Allow 8 Hours for Complete Cure Time
- Use Every 1-2 Months

#### MAIN APPLICATIONS:

- Automotive Paint
- Gel Coat
- Ceramic Coated Surfaces
- Paint Protection Films (PPF)
- Glass
- Chromed Parts and Surfaces
- Aluminum and Coated Aluminum



### LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

#### **TYPICAL PHYSICAL CHARACTERISTICS:**

| PROPERTIES   | ASTM | TYPICAL |
|--------------|------|---------|
| Density      |      | 0.992   |
| рН           |      | 6.1     |
| Conductivity |      | 0       |
|              |      |         |
|              |      |         |
|              |      |         |
|              |      |         |
|              |      |         |
|              |      |         |
|              |      |         |
|              |      |         |

These characteristics are typical of current production. However, slight variations in these characteristics may occur.

#### HEALTH, SAFETY AND ENVIRONMENT:

Health and Safety information is available on the appropriate Safety Data Sheet, which can be obtained from <u>LucasOil.com</u>

Contains Oxirane, 2-methyl-, polymer with oxirane, mono (2propylheptyl) ether. For more ingredient information visit Lucasoil.com/products/appearance/ceramic-speed-wax. Avoid eye contact. Wash hand thoroughly after handling. IF IN EYES: Rinse with water for several minutes. If irritation persists, get medical attention. Keep out of reach of children.

# ADDITIONAL PRODUCTS AND INFORMATION:

For additional product information visit LucasOil.com