



LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET



SURE START PREMIUM STARTING FLUID

Lucas Sure Start Premium Starting Fluid is a 50% ether blend, more than the leading national brand. Helps start stubborn engines fast in cold weather, saves batteries and contains upper cylinder lubricant. Performs to -65°F. For use in passenger cars, diesel engines, lawn mowers, chain saws, outboard motors and fractional horsepower engines. This diesel fuel additive complies with federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.

PART NUMBER AND SIZE:

11238 – Net Wt. 10.7 oz

FEATURES AND BENEFITS:

- Gasoline or Diesel
- Helps Start Stubborn Engines

INSTRUCTIONS:

For diesel engines with glow plugs or preheat manifolds: Follow directions in owner's manual or use as directed by the engine manufacturer.

For gasoline engines:

- 1) Do not flood engine before using.
- 2) Spray with a short burst into carburetor or air intake. Do not overuse product.
- 3) Start engine in normal manner. Do not spray while starting.
- 4) If engine fails to start, repeat procedure for a maximum of three times.

MAIN APPLICATIONS:

For use in passenger cars, diesel engines, lawn mowers, chain saws, outboard motors and fractional horsepower engines.



LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

TYPICAL PHYSICAL CHARACTERISTICS:

PROPERTIES	TYPICAL
Flash Point	-75 °F
Boiling Point	-44 °F
Specific Gravity	Not Determined
Appearance	Clear, Colorless Liquid
Odor	Ether Like
Flammability	Very Flammable
Plastic Safe	Yes
Propellant	A-85

These characteristics are typical of current production. However, slight variations in these characteristics may occur.

HEALTH, SAFETY AND ENVIRONMENT:

DANGER: VAPOR HARMFUL. EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. EYE AND SKIN IRRITANT. Avoid breathing vapor, may cause drowsiness if inhaled. Harmful or fatal if swallowed, do not induce vomiting, CALL A PHYSICIAN IMMEDIATELY. Avoid prolonged contact with skin and eyes. Keep away from heat, sparks, and fire. Heat may cause bursting. Keep away from radiators and stoves. Keep out of prolonged direct sunlight. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F (49°C). KEEP OUT OF REACH OF CHILDREN.

FIRST AID: In case of skin or eye contact, flush with water for 15 minutes. Use with adequate ventilation. If inhaled, move to fresh air – call a physician if symptoms develop or persist. If swallowed, DO NOT INDUCE VOMITING – call a physician immediately. Refer to SDS for complete safety and health information.

CONTAINS: Diethyl Ether (CAS # 60-29-7), Heptane (CAS# 142-82-5), Liquefied Petroleum Gas (CAS # 68476-86-8) and Carbon Dioxide (CAS # 124-38-9).

DISPOSAL: Dispose of empty container in accordance with local, state, and federal regulations.

⚠ WARNING: This product can expose you to chemicals including Chloroethane, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Health and Safety information is available on the appropriate Safety Data Sheet, which can be obtained from LucasOil.com

LINKS AND ADDITIONAL INFORMATION:

SDS:

Product Image: [Click Here](#)

Product Label: [Click Here](#)

Product Flyer:

MPD: [Click Here](#)